



Hazard Mitigation Assistance Guidance Addendum

Hazard Mitigation Grant Program, Pre-Disaster Mitigation
Program, and Flood Mitigation Assistance Program

February 27, 2015



FEMA

Federal Emergency Management Agency
Department of Homeland Security
500 C Street, S.W.
Washington, DC 20472

E. Structure Elevation

Part E of the Addendum supplements the information provided in Parts I through IX of the HMA Guidance. The project-specific guidance in this section does not provide all of the information necessary to apply for funding through an HMA program and must be read in conjunction with all other relevant sections of this guidance. See Part IX, C of the HMA Guidance for additional resources on structure elevation.

E.1 Overview

Structure elevation activities generally involve physically raising an existing structure to an elevation at the BFE or higher if required by FEMA or local ordinance. Structure elevation may be achieved through a variety of methods, including elevating on continuous foundation walls; elevating on open foundations, such as piles, piers, posts, or columns; and elevating on fill. Foundations must be designed to properly address all loads and be appropriately connected to the floor structure above, and utilities must also be properly elevated. Buildings proposed for elevation must be structurally sound and capable of being elevated safely.

E.2 Additional Project Eligibility Requirements

At a minimum, FEMA requires Applicants and subapplicants to design all structure elevation projects in accordance with the NFIP standards in 44 CFR Part 60. For additional information about the NFIP and structure elevation projects, see Part III, E.7 of the HMA Guidance.

FEMA requires Applicants and subapplicants to design all structure elevation projects in accordance with ASCE 24-14, or latest edition, or its equivalent as minimum design criteria.

E.2.1 Eligible Design Standards

Buildings proposed for structure elevation must be structurally sound and capable of being elevated safely. Important design considerations for structure elevations consistent with 44 CFR Part 60 are as follows:

- ◆ The lowest floor of the structure must be elevated to the BFE or to the elevation specified in the local ordinance if higher. Upon completion of the elevation work, an Elevation Certificate (FEMA Form 81-31) verifying “as built” elevations must be completed to ensure that the structure complies with the local floodplain ordinance and NFIP floodplain management and HMA requirements.
- ◆ Elevation projects must be designed and adequately anchored to prevent flotation, collapse, and lateral movement of the structure due to hydrodynamic and hydrostatic loads, including the effects of buoyancy. It is recommended that an engineer certify that the design elevation will withstand the depth and velocity of 100-year flood events (hydrostatic and hydrodynamic loads), any potential increase in wind load, or any other relevant load factors.

-
- ◆ For elevation projects in Zone V with open foundations (piles, piers, posts, or columns), the space below the lowest floor must be free of obstructions or constructed with non-supporting breakaway walls, open wood lattice-work, or screening intended to collapse under wind and water loads without causing collapse, displacement, or other structural damage to the elevated portion of the building or supporting foundation system. Guidance on free-of-obstruction and breakaway wall requirements is available in FEMA Technical Bulletin (TB) 5, *Free-of-Obstruction Requirements* (2008), and FEMA TB-9, *Design and Construction Guidance for Breakaway Walls Below Elevated Coastal Buildings* (2008).
 - ◆ For elevation projects on continuous foundation walls with fully enclosed areas below the lowest floor, the area must be used solely for parking of vehicles, building access, or storage as identified in 44 CFR Section 60.3(c)(5).
 - ◆ Elevation projects on continuous foundation walls must be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwaters. Designs to meet these criteria must be certified by a registered Professional Engineer or meet or exceed the criteria in 44 CFR Section 60.3(c)(5). Guidance on meeting this requirement can be found in FEMA TB-1, *Openings in Foundation Walls and Walls of Enclosures* (2008).

E.3 Elevation Project Application Package

In addition to the items identified in Part IV, H of the HMA Guidance, the following data are required for each structure:

- ◆ Physical address and property owner's name
- ◆ Estimated cost to elevate each structure
- ◆ Name and location of flooding source (e.g., creek, river, watershed, or location of stormwater ponding) and location on the applicable Flood Insurance Rate Map
- ◆ The proposed elevation of the lowest floor for each structure to be mitigated, the BFE, and the current elevation of the lowest finished floor
- ◆ Type of existing foundation (slab-on-grade, crawl space, basement, or open foundation) and the proposed elevation method and standard to be used
- ◆ A statement that the project will be designed in compliance with NFIP standards in 44 CFR Part 60

E.4 Implementation

Elevation project implementation entails pre-construction activities, construction, inspection of the completed foundation and engineering certification, and obtaining a Certificate of Occupancy. Before construction of the foundation begins, it is very important to conduct an inspection of the condition of the structure, survey the site, and complete a soil inspection to make sure the proposed elevation project is feasible on the site.

E.4.1 Elevation Methods

Standard structure elevation methods are identified in FEMA P-312, *Homeowner's Guide to Retrofitting – Third Edition* (2014), and FEMA P-347, *Above the Flood: Elevating Your Floodprone House* (2000). In addition, FEMA has developed guidance for the design of appropriate foundations based on the requirements of the International Codes and other applicable standards. This guidance is provided in FEMA P-550, and is available for use with HMA structure elevation projects. Furthermore, FEMA requires Applicants and subapplicants to design all structure elevation projects in accordance with ASCE 24-14, or latest edition.

Available elevation methods, which are thoroughly described in FEMA P-312, Chapter 5, and FEMA P-347 include:

- ◆ Elevating the existing structure on piles, posts, or piers
- ◆ Filling in the basement and replacing it with an elevated floor
- ◆ Elevating by vertically extending the foundation walls of the home

Activities that result in the construction of new living space at or above the BFE are considered only when they are consistent with mitigation reconstruction requirements described in Addendum Part E.2.1. Activities include structure elevations that abandon a lower enclosed area and add a second story above the BFE to an existing structure.

The method that is selected for elevating a house depends on factors such as:

- ◆ Foundation type
- ◆ Condition of the house
- ◆ Applicable State and local building codes
- ◆ Soil type and bearing capacity
- ◆ Weight of the house and lateral forces on the house from water and other natural hazards, such as winds and earthquakes
- ◆ Height of proposed elevation above the grade level
- ◆ Number of additions to the original structure

The most common foundation types are:

-
- ◆ Crawl space on foundation walls
 - ◆ Slab-on-grade
 - ◆ Open type foundation – piles and posts or piers

Additional details to consider when constructing an elevation project can be found in the following publications:

- ◆ FEMA P-55, *Coastal Construction Manual*, Fourth Edition (2011)
- ◆ FEMA P-259, *Engineering Principles and Practices of Retrofitting Floodprone Structures* (2012)
- ◆ FEMA P-499, *Home Builders Guide to Coastal Construction Technical Fact Sheet Series* (2010)
- ◆ ASCE 24-14, *Flood Resistant Design and Construction* (2014), or latest edition

This list is not a comprehensive list of publications on retrofitting and elevations. More documents are available at <http://www.fema.gov/building-science-publications>.

E.4.2 Eligible Structure Elevation Costs

Allowable costs are costs that are necessary and reasonable for the proper and efficient performance and administration of the Federal award. The following costs associated with structure elevation projects are generally allowable:

- ◆ Engineering services for design, structural feasibility analysis, and cost estimate preparation
- ◆ Surveying, soil sampling, completion of Elevation Certificate, title search, deed recordation fees, legal and/or permitting fees, project administration, and construction management
- ◆ Disconnection of all utilities
- ◆ Building of a foundation so that the lowest floor is at the BFE or higher if required by local ordinance or FEMA
- ◆ Physical elevation of the structure and subsequent lowering and attachment of the structure onto a new foundation
- ◆ Construction of a floor system that meets minimum building code requirements when the existing floor system cannot be elevated or is not appropriate for the new foundation
- ◆ Reconnecting utilities and extending lines and pipes as necessary and elevating all utilities and service equipment
- ◆ Debris disposal and erosion control
- ◆ Costs for repair of lawns, landscaping, sidewalks, and driveways if damaged by elevation activities

-
- ◆ Construction of a utility room above the BFE only if there is no existing space within the house for this purpose or there is no alternative cost-effective way to elevate the utilities
 - ◆ Elevation of existing decks, porches, or stairs
 - ◆ Construction of new stairs, landings, and railings to access the elevated living space per minimum code or local ordinance
 - ◆ Construction of ADA-compliant access facilities or ramps when an owner or a member of the owner's family has a permanent disability and a physician's written certification. An ADA-compliant access to ingress/egress is allowable for funding unless specified otherwise in applicable State or local codes (for more information on ADA, see <http://www.ada.gov>). If ramps are not technically feasible, a mechanical chair lift may be installed.
 - ◆ Documented reasonable living expenses (except food and personal transportation) that are incurred while the owner is displaced by the elevation construction
 - ◆ Abatement of asbestos and lead-based paint
 - ◆ Filling basements with compacted clean fill

E.4.3 Ineligible Structure Elevation Costs

Certain structure elevation activities and their associated costs are not eligible. Ineligible costs for structure elevation include, but are not limited to, the following:


- ◆ Elevating structures that were not in compliance with current NFIP standards at the time of construction
- ◆ Costs related to building additions or auxiliary structures
- ◆ Construction of new decks or porches
- ◆ Any improvements for purely aesthetic reasons, unless required by the EHP compliance review
- ◆ Costs to replace or repair utility service components that are undersized, inadequately designed, or unsafe, unless required by code (except utility rooms noted as eligible costs)
- ◆ Exterior finish on the exposed foundation of the elevated building, unless required by EHP compliance review and or local code
- ◆ Additional landscaping for ornamentation beyond what existed on the site prior to construction of the project (e.g., trees, shrubs)

E.4.4 Survey and Inspection Considerations

Surveying and inspections are encouraged throughout the construction process. Certifications of the surveys ensure that the work has been performed in compliance with the structure-specific plans and specifications, applicable codes and standards, and minimum NFIP requirements.

Figure 1 identifies important inspection and survey considerations.

Figure 1: Inspection and Survey Considerations



E.5 Elevation Closeout

In addition to the typical HMA closeout procedures, closeout of structural elevation projects generally includes:

- ◆ Update of the property site information in the respective HMA system (i.e., eGrants or NEMIS) database for each structure
- ◆ A Certificate of Occupancy for each structure in the project to certify that the structure is code-compliant

-
- ◆ A Final Elevation Certificate (FEMA Form 81-31) for each structure to ensure the structure has been elevated to the proper elevation
 - ◆ A copy of the recorded deed amendment for each property as required by Part III, E.7.1 of the HMA Guidance
 - ◆ Certification by an engineer, floodplain manager, or senior local official that the completed structure elevation is in compliance with local ordinances and NFIP regulations, including all applicable NFIP Technical Bulletins
 - ◆ A front, rear, and side photograph of the final elevated structure
 - ◆ Verification of flood insurance for each structure